

Inspur Integrated Drive Ultra-Thin LED Module



With an overall thickness of 1.34cm, slim to the extreme





Integrated Design

Entirely DC-powered, requiring no separate receiver card



Flexible Splicing

Use as a single unit or plug-and-play, whichever you prefer



Module Size (W×H×D) (mm)	320 x 180 x 13.4(With Cabinet)
Brightness (cd/ m²)	800-1000
Color Temperature (K)	6500(2000K ~ 9300K adjustable)
Viewing Angle (H/V)	160°/160 °
Contrast	10000:1
Peak Power Consumption (W/ ㎡)	≤ 330
Average Power Consumption (W/ ㎡)	≤ 99
Power Supply Requirements	AC100 ~ 240V (50-60Hz)
Refresh Rate (Hz)	3840/7680
Depth Of Processing (bits)	15
Typical Value Of Life (h)	≥ 100000
Operating Temperature/ Humidity Range	-20 ° C - 60 ° C / 10%-90%RH (no condensation)
Store Temperature/ Humidity Range	-40 ° C - 70 ° C / 10%-90%RH (no condensation)

Note: The above parameters are for reference only and are not the basis for final delivery. The product can be customized according to requirements

INSPUR INTELLIGENT TERMINAL CO., LTD.

Official Customer Service: +86 531 85105558 Website: https://en.inspur.com
Official Email: IITOS@inspur.com Address: No. 1036, Langchao Road, Lixia District, Ji'nan City, Shandong Province



